

PTFE

Material: 100 % Polytetrafluoroethylene
Thread construction: Continuous filament

No./Tkt.	PTFE 30
Applications	This sewing thread is ideal for making marquees, outdoor textiles and filter.
Advantages	Very good temperature, ultra-violet light and chemical resistance and it shows high breaking strength and abrasive resistance. For short time resilient with up to 300 °C.

Make-up	
Size	ca. 4.200 m | 0,55 kg
Article code	724831
Sales unit	kg
Shade range	9 colours: 111, 106, 450, 351, 365, 386, 402, 38, 1274
Needle size	NM 90 – 110 / 14 – 18

Technology	
Count	No./Tkt. 30 – dtex 1.300(3) – tex 130
Breaking strength	> 3.000 cN
Elongation	∅ 3,5 % (3 % – 4 %)
Thermal shrinkage (160 °C/30 min.)	< 1 %
Maximum permanent heat resistance	250 °C

Shade range

111 | 106 | 450 | 351 | 365 | 386 | 402 | 38 | 1274

Please note: The indicated technical information is based on average values and should only serve as a point of reference.

www.guetermann.com
Headquarters Europe: Gütermann GmbH | 79261 Gutach-Breisgau, Germany | Tel. +49 7681 21-0 | contact@guetermann.com

OV2522